



02166479486  
0912 8448763  
0919 0345384

تماس 24 ساعته حتی تعطیلات



PMBC



PHDB



FCBF

## Acrylic Miniature Flow meters - PMBC

### Technical Specifications

Water	0,6...6l/h-25...250l/h
Air	0,05...0,5NI/m-10...100NI/m
Connection Size	G 1/4" or NPT
Body-Connection	SS316
Temperature	-10...60°C
Pressure	10 bar max.
Accuracy	<±3% F.S.
Application	Air, Nitrogen, Water

### Features

- Easy To Install
- Lower Cost
- Easy Readable Scale



Bass Instruments, PMBC Series Miniature Acrylic Flow meters are low cost and small size flow meters designed to measure instant flow of gases such as air and nitrogen. With the standard adjustment valve, you can fix the flow to the desired amount. Connection parts can be made of optional AISI 316 material.

تماس 24 ساعته حتی تعطیلات

Tel ۰۲۱ ۶۶۴۷ ۹۴۸۶

مدیریت ۰۹۱۲ ۸۴۴ ۸۷۶۳

شبکه های مجازی / ارسال استعلام ۰۹۳۵ ۴۴ ۷۹ ۱۱۰

تلگرام / سروش @ Controltak

Fax ۰۲۱ ۸۹۷۷ ۹۳۷۳

www.Controltak.com

Controltak@chmail.ir

Controltak@gmail.com

اینستاگرام Control-Tak

## Admirable Air Flow Meter - PHDB

### Technical Specifications

<b>Measuring Range-Water</b>	1 - 10 Nm <sup>3</sup> /h ... 80 - 400 Nm <sup>3</sup> /h
<b>Connection Size</b>	Threaded 1/2", 1"
<b>Body-Connection</b>	Acrylic- ABS Plastic
<b>Temperature</b>	0...60°C max.
<b>Pressure</b>	10 bar max.
<b>Accuracy</b>	<±4% F.S.
<b>Application</b>	Air, Nitrogen



### Features

**Easy Mounting**

**Optional Different Scales**

**Low Cost Scale**

**Large Scale for Easy Reading**

Bass Instruments, PHDB Series Variable Area Float Flow Meters are low cost flow meter designed to measure instant flow of fluids such as air or nitrogen. Light and durable with complete plastic design. Ph. dB Debi meters with threaded connections can be connected to the installation in a very short time. In plastic products, resistance temperature and resistance pressure are inversely proportional. Please consult during product selection.

تماس 24 ساعته حتی تعطیلات

Tel ۰۲۱ ۶۶۴۷ ۹۴۸۶

مدیریت ۰۹۱۲ ۸۴۴ ۸۷۶۳

شبكة های مجازی / ارسال استعلام ۰۹۳۵ ۴۴ ۷۹ ۱۱۰

تلگرام / سروش @Controltak

Fax ۰۲۱ ۸۹۷۷ ۹۳۷۳

www.Controltak.com

Controltak@chmail.ir

Controltak@gmail.com

اینستاگرام Control-Tak

## Glass Tube Miniature Flow meters - FBCF

### Technical Specifications

<b>Measuring Range WATER</b>	0, 25 - 2,5 l/h... 16 - 160 l/h/min
<b>Measuring Range Air</b>	0,5 - 5 l/h ... 430 - 4300 l/h/min
<b>Connection Size</b>	G 1/8"-F/sa
<b>Body-Connection</b>	Borosilicate Glass - AISI304
<b>Temperature</b>	120°C max.
<b>Pressure</b>	10 bar max.
<b>Accuracy</b>	<±2,5% T.S.
<b>Application</b>	Liquid and Gases



### Features

- Easy To Install
- Low Cost
- Easy Readability Scale

Bass Instruments, Mini float flow meter with FBCF Series glass tube, are used to measure instant flow of partially abrasive and high temperature low flow fluids. Measuring Tube borosilicate glass, connections are made of stainless steel. Standard flow adjustment valve is available. There is a plexi protection casing protecting the flow tube at the front. The fluid you will measure must definitely be filtered before the flow meter.

تماس 24 ساعته حتی تعطیلات

Tel ۰۲۱ ۶۶۴۷ ۹۴۸۶

مدیریت ۰۹۱۲ ۸۴۴ ۸۷۶۳

شبكة های مجازی / ارسال استعلام ۰۹۳۵ ۴۴ ۷۹ ۱۱۰

تلگرام / سروش @ Controltak

Fax ۰۲۱ ۸۹۷۷ ۹۳۷۳

www.Controltak.com

Controltak@chmail.ir

Controltak@gmail.com

اینستاگرام Control-Tak