



02166479486

0912 8448763

0919 0345384

تماس 24 ساعته حتی تعطیلات

شرکت فنی مهندسی کنترل تک پیشرو در صنعت ابزار دقیق



Protected Glass Tube Flow meters - PTYP

Technical Specifications

Measuring Range-Water 4 - 40 l/h. ... 4 - 16 m³/h

Measuring Range-Air 0,12 - 1,2 Nm³/sa. ... 30 - 300 Nm³/sa.

Connection Size DN15...DN50 Threaded, Flanged or Hygienic

Body-Connection Borosilicate Glass-AISI316 Stainless Steel

Temperature -20...120°C max.

Pressure 10 Bar max.

Accuracy $\pm 2\%$ T.S.

Application Water, Air and so on



Features

Robust Design

Stainless Steel Welded

Insulated Stainless Steel Measuring Tube

Measuring Accuracy

Flanged, Threaded or Hygienic Connection According To The Process

Bass Instruments, PTYP Series Protected Glass Tube Flow meters are high precision and rugged designed flow meters designed to measure the instant flow of liquids such as water or water, as well as gases such as air or nitrogen. PTYP Series protected glass tube flow meters with flange, threaded or hygienic clamp connections can be connected to the installation in a very short time. With its high temperature resistance and measuring tube housing, it is easily resistant to many difficult conditions.

تماس 24 ساعته حتی تعطیلات

Tel ۰۲۱ ۶۶۴۷ ۹۴۸۶

مدیریت ۰۹۱۲ ۸۴۴ ۸۷۶۳

شبکه های مجازی / ارسال اعلام ۰۹۳۵ ۴۴ ۷۹ ۱۱۰

تلگرام / سروش @ Controltak

Fax ۰۲۱ ۸۹۷۷ ۹۳۷۳

www.Controltak.com

Controltak@chmail.ir

Controltak@gmail.com

اینستاگرام Control-Tak

Acrylic Miniature Flow meters - PMBC

Technical Specifications

Water	0,6...6l/h-25...250l/h
Air	0,05...0,5NI/m-10...100NI/m
Connection Size	G 1/4" or NPT
Body-Connection	SS316
Temperature	-10...60°C
Pressure	10 bar max.
Accuracy	<±3% F.S.
Application	Air, Nitrogen, Water

Features

- Easy To Install
- Lower Cost
- Easy Readable Scale



Bass Instruments, PMBC Series Miniature Acrylic Flow meters are low cost and small size flow meters designed to measure instant flow of gases such as air and nitrogen. With the standard adjustment valve, you can fix the flow to the desired amount. Connection parts can be made of optional AISI 316 material.

تماس 24 ساعته حتی تعطیلات

Tel ۰۲۱ ۶۶۴۷ ۹۴۸۶

مدیریت ۰۹۱۲ ۸۴۴ ۸۷۶۳

شبکه های مجازی / ارسال استعلام ۰۹۳۵ ۴۴ ۷۹ ۱۱۰

تلگرام / سروش @ Controltak

Fax ۰۲۱ ۸۹۷۷ ۹۳۷۳

www.Controltak.com

Controltak@chmail.ir

Controltak@gmail.com

اینستاگرام Control-Tak

Glass Tube Miniature Flow meters - FBCF

Technical Specifications

Measuring Range	0,25 - 2,5 l/h... 16 - 160 l/h/min
Measuring Range Air	0,5 - 5 l/h ... 430 - 4300 l/h/min
Connection Size	G 1/8"-F/sa
Body-Connection	Borosilicate Glass - AISI304
Temperature	120°C max.
Pressure	10 bar max.
Accuracy	<±2,5% T.S.
Application	Liquid and Gases



Features

Easy To Install

Low Cost

Easy Readability Scale

Bass Instruments, Mini float flow meter with FBCF Series glass tube, are used to measure instant flow of partially abrasive and high temperature low flow fluids. Measuring Tube borosilicate glass, connections are made of stainless steel. Standard flow adjustment valve is available. There is a plexi protection casing protecting the flow tube at the front. The fluid you will measure must definitely be filtered before the flow meter.

تماس 24 ساعته حتی تعطیلات

Tel ۰۲۱ ۶۶۴۷ ۹۴۸۶

مدیریت ۰۹۱۲ ۸۴۴ ۸۷۶۳

شبكة های مجازی / ارسال استعلام ۰۹۳۵ ۴۴ ۷۹ ۱۱۰

تلگرام / سروش @ Controltak

Fax ۰۲۱ ۸۹۷۷ ۹۳۷۳

www.Controltak.com

Controltak@chmail.ir

Controltak@gmail.com

اینستاگرام Control-Tak

Panel Mount Acrylic Flow meters - POBC

Technical Specifications

Measuring Range-Water	2 - 18 l/min. ... 30 - 170 l/min
Connection Size	Female 1/2", 3/4", 1"
Body-Connection	Acrylic-ABS plastic
Temperature	-10...60°C max.
Pressure	10 bar max.
Accuracy	<±3% F.S.
Application	Liquids

Features

Easy To Install

Low Cost

Easy Readability Scale



Bass Instruments, POBC Series Acrylic Flow meter are low cost Flow meter designed to measure instant flow of fluids with similar properties to water or water. There are two models where you can only read or adjust the flow with the help of the adjustment valve. Connection parts can be made of optional AISI 316 material.

تماس 24 ساعته حتی تعطیلات

Tel ۰۲۱ ۶۶۴۷ ۹۴۸۶

مدیریت ۰۹۱۲ ۸۴۴ ۸۷۶۳

شبكة های مجازی / ارسال استعلام ۰۹۳۵ ۴۴ ۷۹ ۱۱۰

تلگرام / سروش @ControItak

Fax ۰۲۱ ۸۹۷۷ ۹۳۷۳

www.ControItak.com

ControItak@chmail.ir

ControItak@gmail.com

اینستاگرام Control-Tak

Technical Specifications

Measuring Range-Water	0,1 - 1 l/min. ... 200 - 2000 l/min.
Measuring Range-Air	0,12 - 1,2 Nm ³ /h. ... 50 - 500 Nm ³ /h
Connection Size	DN10...DN125 Flanged
Links	AISI304, AISI316, PVC, PVDF
Measuring Tube	P.C. , Borosilicate
Temperature	-10...100°C max.
Pressure	10 Bar max.
Accuracy	<±2,5% F.S.
Output	Optional Single or Double Contact
Application	Water, Air and so on



Features

Robust Design

Alternative Connection Options

Wide Range Of Measuring Points

Ideal For Chemical Applications

Bass Instruments, NTYP Series Variable Area Float Flow meters are high-precision and rugged flow meters designed to measure the instantaneous flow of liquids such as water or water, as well as gases such as air or nitrogen. NTYP Series variable area float flow meters with flanged connections can be connected to the installation in a very short time. With its high temperature resistance and measuring tube housing, it is easily resistant to many difficult conditions

تماس 24 ساعته حتی تعطیلات

Tel ۰۲۱ ۶۶۴۷ ۹۴۸۶

مدیریت ۰۹۱۲ ۸۴۴ ۸۷۶۳

شبکه های مجازی / ارسال استعلام ۰۹۳۵ ۴۴ ۷۹ ۱۱۰

تلگرام / سروش @ Controltak

Fax ۰۲۱ ۸۹۷۷ ۹۳۷۳

www.Controltak.com

Controltak@chmail.ir

Controltak@gmail.com

اینستاگرام Control-Tak